

PRODUCT: MAXIM™ Quick N Firm Seam Sealer

PART NUMBER: 100821 10.3 oz. (305mL) Cartridge 6 units/case

DESCRIPTION: Maxim™ Quick N Firm seam sealer is a single component, firm setting and fast drying seam sealer. It adheres well to primed or painted steel, galvanized, aluminum, SMC and fiberglass. It is excellent at sealing interior and exterior joints.

FEATURES & BENEFITS:
Easy to use
Excellent gunability
Flexible
Excellent adhesion to many substrates
Non-sag and fast skinning
Paintable in 30 minutes

PREPARATION: Prepare area by removing grease, oil, dust or other contaminants. Wipe with a dry rag. Sand area with 180-220 grit sand paper. Do not remove factory e-coat. Apply primer surfacer according to paint manufacturer's recommendation. Sand primer surface with 320 grit sand paper. Re-clean with a mild solvent or wax and grease remover.

APPLICATION: Apply steady pressure to the caulking gun at all times during application. Tool Maxim Quick N Firm seam sealer to match the OEM seam. Product can be beaded, brushed or spread out. Solvent may be used to smooth the surface. Can be topcoated in 30 minutes at 72°F. Thicker applications may require longer dry times.

TECHNICAL SPECIFICATIONS:

▪ Appearance	Beige
▪ Skin Over Time	9 minutes
▪ Working Time	15 minutes
▪ Paint Time	30 minutes
▪ Full Cure	24 hours

NOTE: Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

For professional use only, read all directions and warnings prior to using Evercoat® products. Keep cartridge closed and store in a cool dry place.

Safety Data Sheets can be found online at evercoat.com.